



IS:5290  
  
 CM/L-3018943

## SINGLE HEADED LANDING VALVE

Material : Stainless Steel  
 Size : 63mm (Female), single outlet type - "A" ISI  
 Hydraulic Test : Tested at 21 Kgf/cm<sup>2</sup>  
 Water tightness : Tested at 14 Kgf/cm<sup>2</sup>

## DOUBLE HEADED LANDING VALVE

Material : Stainless Steel  
 Size : 63mm (Female), Double outlet type - "B" ISI  
 Hydraulic Test : Tested at 21 Kgf/cm<sup>2</sup>  
 Water tightness : Tested at 14 Kgf/cm<sup>2</sup>



IS:5290  
  
 CM/L-3018943

## FIRE HOSE DELIVERY COUPLING

Material : Stainless Steel  
 Size : 63mm, 52mm, 38mm dia  
 Hydraulic Test : Tested at 21 Kgf/cm<sup>2</sup>  
 Water tightness : Tested at 14 Kgf/cm<sup>2</sup>



IS:903  
  
 CM/L-8700117114

## SHORT BRANCH PIPE WITH NOZZLE

Material : Stainless Steel  
 Size : 63mm dia inlet  
 20mm dia outlet  
 Hydraulic Test : Tested at 21 Kgf/cm<sup>2</sup>  
 Water tightness : Tested at 14 Kgf/cm<sup>2</sup>



IS:903  
  
 CM/L-8700117114

## First Aid Hose Reel Drum

### Specification

- Type Swinging 180° wall mounted
- Size : Inlet 20mm (3/4") BSP thread size
- Confirming Specification IS:884

IS: 884  




## Compact Type Hose Reel Drum

### Features

- Corrosion Free
- Powder Coated
- Light Weight
- IS:12585 Hose Reel Pipe with Bursting Pressure 14kg/cm<sup>2</sup>
- Hydraulically clamped CE Marked Nozzle



## Thermoplastic Hoses For Hose Reels

- 3 Layered, Non-crackable
- Kink, Abrasion & Flame Resistant
- Excellent Pressure Sustainability
- Anti Ageing & Non-Corrosive
- Puncture & Crush Resistant
- Light weight - easy to use
- Both ends sealed for puncture-free test
- Fluted finish for better grip
- Non-sticky even in hot weather
- Recyclable, so Eco-friendly
- Meter marking on every meter

IS:12585

